

产品大类	标准号	代表牌号	厚度	宽度	用途及特点
高强度无间隙原子钢	Q/ASB 89	170P1	0.6-2.0	900-1580	<p>冲压用，具有良好的冲压性能同时有高的强度，对部件减薄有利，适用于对抗凹陷性能有较高要求的零部件，主要用于汽车面板冲压用或深冲用。</p> <p>With excellent drawing capability, high strength and favorableness in part thickness reduction, they are used for drawing purposes and suitable to manufacturing parts with relatively high requirements for dinge-resistant performance.</p>
		210P1			<p>一般用，有高的强度，对部件减薄有利，适用于对抗凹陷性能有较高要求的零部件，主要用于汽车内部结构件一般用或冲压用。</p> <p>With high strength and favorableness in part thickness reduction, they are used for commercial purposes and suitable to manufacturing parts with relatively high requirements for dinge-resistant performance. With high strength and favorableness in part thickness reduction, they are used for commercial purposes and suitable to manufacturing parts with relatively high requirements for dinge-resistant performance.</p>
		250P1			<p>结构用，有高的强度，对部件减薄有利，适用于制作抗凹陷性能有较高要求的零部件，主要用于汽车内部结构件结构用或一般用。</p> <p>With high strength and favorableness in part thickness reduction, they are used for structural purposes and suitable to manufacturing parts with relatively high requirements for dinge-resistant performance.</p>